

Sales Bulletin July 2017

## Sensys Blind Corner Inset - Soft Close

95° Clip-on hinge with Dowels for Corner Cabinets



- Clip on Installation, with Dowels
- For door thickness 15 28mm
- Cup Diameter: 35mm, Cup Depth: 12.8mm
- Integrated adjustment of door offset: +1mm / -2mm
- Integrated reveal adjustment +3mm / -2mm
- Height adjust mounting plates +/- 2mm
- 20 lb/pr. rating fewer hinges needed for oversized doors
- Made in Germany

<u>Code</u>	<u>Ctn</u>	<u>List/ea</u>
9088045	50	\$ 9.80

## Minimum reveal per door

Door	Cup distance C mm								
thickness mm	3.0	4.0	4.5	5.0	6.0	7.0			
15	0.2	0.2	0.2	0.2	0.2	0.2			
16	0.3	0.3	0.3	0.3	0.3	0.3			
17	0.4	0.4	0.4	0.4	0.4	0.4			
18	0.6	0.6	0.6	0.6	0.6	0.5			
19	8.0	8.0	8.0	8.0	0.7	0.7			
20	1.1	1.0	1.0	1.0	1.0	0.9			
21	1.4	1.3	1.3	1.3	1.2	1.2			
22	2.2	1.8	1.7	1.6	1.6	1.5			
23	3.0	2.6	2.4	2.2	2.0	1.9			
24	3.9	3.4	3.2	3.0	2.6	2.4			
25	4.8	4.2	4.0	3.8	3.4	3.0			
26	5.7	5.1	4.8	4.6	4.2	3.8			
27	6.6	6.0	5.7	5.5	5.0	4.5			
28	7.5	6.9	6.6	6.3	5.8	5.3			

Please note:

The table entries refer to doors with an edge radius of 1 mm.


On doors with other radii, the minimum reveal changes as follows:

Radius 0 mm:

Values shown in table + 0.4 mm

Radius 3 mm:

Values shown in table - 0.6 mm



Distance D = 4mm - door offset (recommended door offset equals 1mm)

		-		6.5 7.5
			8	Po-
2 2				
				<del>-</del>
*	(LR 20 x 32)* LR 37 (LR 28)*	[[R20×32]*		
		F	- с	15 - 28
≥ 15	72	x -		

Dealer No. B/C

Determining hole line distance X mm when using mounting plate for hole line 3											
Reveal	Cup d	Cup distance C mm									
mm	3.0	3.5	4.0	4.5	5.0	5.5	6.0	7.0			
0.5	35.0	34.5	34.0	33.5	33.0	32.5	32.0	31.0			
1.5	34.0	33.5	33.0	32.5	32.0	31.5	31.0	30.0			
2.5	33.0	32.5	32.0	31.5	31.0	30.5	30.0	29.0			
3.5	32.0	31.5	31.0	30.5	30.0	29.5	29.0	28.0			
4.5	31.0	30.5	30.0	29.5	29.0	28.5	28.0	27.0			
5.5	30.0	29.5	29.0	28.5	28.0	27.5	27.0	26.0			
6.5	29.0	28.5	28.0	27.5	27.0	26.5	26.0	25.0			
7.5	28.0	27.5	27.0	26.5	26.0	25.5	25.0	24.0			